



## Specifications LED Tracklight ELARA PC White 30W 2500lm 40D - 830 Warm White

[View Product](#)

### General Information

|                          |  |
|--------------------------|--|
| SKU                      | 247568                                       |
| EAN                      | 8720701845680                                |
| Brand                    | Other  |
| Manufacturer Name        | 3-PHASE RAIL SPOTLIGHT ELARA 30W WHITE 3000K |
| Any Lamp all-in warranty | 5 Years                                      |
| Average Lifetime (h)     | 50000  |

### Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Technology                  | LED Integrated  |
| Wattage                     | 30              |
| Replaces (Watt)             | 90              |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Not Dimmable    |
| Colour Code                 | 830 Warm White  |
| Colour temperature (Kelvin) | 3000 Warm White |
| Colour Rendering (Ra)       | 80-89           |
| Colour of Light             | White           |
| Light colour options        | Single Color    |
| Luminous Flux (Lumen)       | 2500            |
| Luminous Efficacy (lm/W)    | 85              |

|                    |                   |
|--------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
|--------------------|-------------------|

|                     |    |
|---------------------|----|
| Beam Angle (degree) | 40 |
|---------------------|----|

|              |       |
|--------------|-------|
| Power factor | >0.90 |
|--------------|-------|

|                       |               |
|-----------------------|---------------|
| Product Type Category | LED Trackspot |
|-----------------------|---------------|

## Fixture Information

|                |     |
|----------------|-----|
| Including bulb | Yes |
|----------------|-----|

|                 |      |
|-----------------|------|
| Mounting Method | Rail |
|-----------------|------|

|                    |              |
|--------------------|--------------|
| Fixture Connection | 3-Phase rail |
|--------------------|--------------|

|                       |            |
|-----------------------|------------|
| Operating Temperature | -20 to +40 |
|-----------------------|------------|

|           |      |
|-----------|------|
| IP-rating | IP22 |
|-----------|------|

|                        |                   |
|------------------------|-------------------|
| Impact Protection (IK) | IK05 - 0.70 joule |
|------------------------|-------------------|

|         |                    |
|---------|--------------------|
| Housing | PC (Polycarbonate) |
|---------|--------------------|

|                       |       |
|-----------------------|-------|
| Colour of the Fixture | White |
|-----------------------|-------|

|                    |       |
|--------------------|-------|
| Colour of material | White |
|--------------------|-------|

|               |                    |
|---------------|--------------------|
| Optical Cover | PC (Polycarbonate) |
|---------------|--------------------|

|        |       |
|--------|-------|
| Series | ELARA |
|--------|-------|

## Dimensions

|             |    |
|-------------|----|
| Length (mm) | 90 |
|-------------|----|

|            |    |
|------------|----|
| Width (mm) | 90 |
|------------|----|

|             |     |
|-------------|-----|
| Height (mm) | 210 |
|-------------|-----|

|               |    |
|---------------|----|
| Diameter (mm) | 90 |
|---------------|----|

 **Sensor Information** Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



Up to **7 years warranty**

No Sensor



**Easy** return process